

CSCI 4333 Design of Database Systems Fall 2023

Section 1 Suggested Solution to Final Examination

[1] (a) For example:

```
SELECT DISTINCT f.facId,
    CONCAT(f.fname, ' ', f.lname) AS faculty,
    d.deptName AS department,
    COUNT(c.classId) AS `Number of classes taught`
FROM faculty AS f LEFT JOIN department AS d USING (deptCode)
    LEFT JOIN class AS c USING (facId)
GROUP BY f.facId, faculty, department
HAVING `Number of classes taught` < 2
ORDER BY `Number of classes taught` DESC;
```

(b)

```
SELECT DISTINCT s.stuId,
    CONCAT(s.fname, ' ', s.lname) AS student,
    s.major
FROM student AS s
WHERE s.minor IS NULL
AND s.stuId NOT IN (SELECT DISTINCT stuId FROM enroll);
```

(c)

```
WITH csci AS
(SELECT e.stuId, COUNT(c.classId) AS csciClasses
 FROM enroll AS e INNER JOIN class AS c USING (classId)
    INNER JOIN course AS co USING (courseId)
 WHERE co.rubric = 'CSCI'
 GROUP BY e.stuId),
cinf AS
(SELECT e.stuId, COUNT(c.classId) AS cinfClasses
 FROM enroll AS e INNER JOIN class AS c USING (classId)
    INNER JOIN course AS co USING (courseId)
 WHERE co.rubric = 'CINF'
 GROUP BY e.stuId)
SELECT DISTINCT s.stuId,
    CONCAT(s.fname, ' ', s.lname) AS student,
    IFNULL(csci.csciClasses, 0) AS `Number of CSCI classes`,
    IFNULL(cinf.cinfClasses, 0) AS `Number of CINF classes`
FROM student AS s LEFT JOIN csci USING (stuId)
    LEFT JOIN cinf USING (stuId);
```

(2)

| | | | | | | | | | | | |
|-----|-----------------------------|-----|---|-----|---|-----|---|-----|---|-----|---|
| (a) | F | (b) | T | (c) | F | (d) | T | (e) | T | | |
| (f) | F (T marginally acceptable) | | | (g) | F | (h) | T | (i) | F | (j) | F |

(3)

(a) R(A,B,C,D) with {A->B, BC->D}

CK: [1] AC; prime: A, C; Highest NF: 1NF; A->B violate 2NF.

(b) R(A,B,C,D) with {A->BC, B->D}

CK: [1] A; prime: A; Highest NF: 2NF; B->D violates 3NF

(c) R(A,B,C,D) with {A->B, B->AC, AB->D}: canonical cover: {A->BCD, B->A}

CK: [1] A, [2] B; prime: A, B; Highest NF: BCNF

(4) For R(A,B,C,D,E) R(A,B,C,D,E) {B->A, BA->D, D->E }

(a) Canonical cover: {B->AD, D->E}

Candidate Key: [1] BC; Prime attributes: B, C

(b) 1NF, as B->A and B->D violate 2NF

(c) R1(A,B,D) {B->AD} in BCNF, R2(D,E) {D->E} in BCNF and R3(B,C) {} in BCNF

(5) For example:

```
print('<h3>Department information</h3>')

#      SQL
query = '''
SELECT DISTINCT d.deptName,
               t1.n_majors,
               t1.majors,
               t2.n_faculty
FROM department AS d,
     (SELECT COUNT(s.stuId) AS n_majors,
        GROUP_CONCAT(CONCAT(s.fname, ' ', s.lname) SEPARATOR ', ') AS majors
      FROM student AS s
      WHERE s.major = %s) AS t1,
     (SELECT COUNT(f.facId) AS n_faculty
      FROM faculty AS f
      WHERE f.deptCode = %s) AS t2
WHERE d.deptCode = %s;
'''

cursor.execute(query, (str(dc), str(dc), str(dc)))
(department, n_majors, majors, n_faculty) = cursor.fetchone()
print(f'The department {department} ({dc}) has \n<ul><li>{n_majors} major students:
{majors}</li><li>{n_faculty} faculty members</li>\n</ul>\n')
```

(6) For example:

```
use toyu
db.student.find(
  { "$and": [ {"advisor": {$ne: null}} ,
              { "ach": {"$gte": 15}},
              { "ach": {"$lte": 35}}] },
  { "stuId": 1,
    "fname": 1,
    "lname": 1,
    "advisor": 1,
    "minor": {"$ifNull": ["$minor", "undeclared"]},
```

```

        "ach_credits": "$ach",
        "_id": 0    }
    )

//
db.student.find(
  { "advisor": {$ne: null} ,
    "ach": {"$gte": 15, "$lte": 35}},
  { "stuId": 1,
    "fname": 1,
    "lname": 1,
    "advisor": 1,
    "minor": {"$ifNull": ["$minor", "undeclared"]},
    "ach_credits": "$ach",
    "_id": 0    }
)

```

(7) (a) BE

Since, for,

1. There are exactly 2 candidate keys.
2. One of the candidate key is A.
3. B and E are prime attributes. C and D may or may not be prime attributes.
4. There are exactly 20 superkeys.

[1] to [3] imply that the second candidate key must contain B and E, such as BE, BEC, BED and BECD. However, only when BE is the second candidate key, there are 20 superkeys.

(b) (i)

StudentId -> Major

DormId -> DormName

DormName -> DormId

StudentId, Semester, Year -> DormId, Room

(ii) CK: {StudentId, Semester, Year}

(iii) 1NF since StudentId -> Major violates 2NF.

(c) The words "modeling" and "goldmine" are anagrams. Other interesting takes will be considered.