

DASC 5333 Database Systems for Data Science
CSCI 4333 Design of Database Systems
Spring 2024
Homework #7

Suggested Solution to Question (1)

For example:

1	Account(<u>Username</u> , Password)
Candidate Keys	[1] Username
Foreign Keys	
Nullable Attributes	
Non-nullable Attributes	Username, Password
Notes	Account(Username, Password)
Normalization Analysis	[FD]: [1] Username -> Password [Highest NF]: BCNF
2	TRMember(<u>TRMemberId</u> , LName, FName, ScreenName, StartTime, EMail, ReferrerTRMemberId, Username)
Candidate Keys	[1] TRMemberId, [2] ScreenName
Foreign Keys	[1] ReferrerTRMemberId references TRMember(TRMemberId), [2] Username references Account(Username)
Nullable Attributes	TRRefererMemberId, EMail
Non-nullable Attributes	TRMemberId, LName, FName, ScreenName, StartTime
Notes	
Normalization Analysis	[FD]: [1] TRMemberId -> LName, FName, ScreenName, StartTime, EMail, ReferrerTRMemberId, Username; [2] ScreenName -> TRMemberId [Highest NF]: BCNF
3	Team(<u>TeamId</u> , TName, Description, Since, OwnerTRMemberId)
Candidate Keys	[1] TeamId
Foreign Keys	[1] OwnerTRMemberId references TRMember(TRMemberId)
Nullable Attributes	Description
Non-nullable Attributes	TeamId, TName, Since, OwnerTRMemberId
Notes	
Normalization Analysis	[FD]: [1] TeamId -> Description, Since, OwnerTRMemberId [Highest NF]: BCNF
4	TeamManager(<u>ManagerId</u> , TRMemberId, TeamId)
Candidate Keys	[1] ManagerId, [2] TRMemberId, TeamId
Foreign Keys	[1] TRMemberId references TRMember(TRMemberId), [2] TeamId references Team(TeamId)
Nullable Attributes	
Non-nullable Attributes	ManagerId, TRMemberId, TeamId
Notes	[1] ManagerId is created as a surrogate primary key.
Normalization Analysis	[FD]: [1] ManagerId -> TRMemberId, TeamId; [2] TRMemberId, TeamId ->

	ManagerId [Highest NF]: BCNF
5	TeamMember(TMId, TRMemberId, TeamId, JointTime)
Candidate Keys	[1] TMId, [2] TRMemberId, TeamId, JointTime
Foreign Keys	[1] TRMemberId references TRMember(TRMemberId), [2] TeamId references Team(TeamId)
Nullable Attributes	
Non-nullable Attributes	TMId, TRMemberId, TeamId, JointTime
Notes	[1] TMId is created as a surrogate primary key.
Normalization Analysis	[FD]: TMId -> TRMemberId, TeamId, JointTime; [2] TRMemberId, TeamId, JointTime -> TMId [Highest NF]: BCNF
6	RoleLevel(RLNum, Definition)
Candidate Keys	[1] RLNum
Foreign Keys	
Nullable Attributes	
Non-nullable Attributes	RLNum, Definition
Notes	
Normalization Analysis	[FD]: [1] RLNum -> Definition [Highest NF]: BCNF
7	Role(RoleId, RLNum)
Candidate Keys	[1] RoleId
Foreign Keys	[1] RLNum references RoleLevel(RLNum)
Nullable Attributes	
Non-nullable Attributes	
Notes	[1] RoleId is created as a surrogate primary key. [2] We used three relations to implement the three classes Role, UserDefinedRole and StandardRole. It is possible to use only one relation.
Normalization Analysis	[FD]: [1] RoleId -> RLNum [Highest NF]: BCNF
8	TeamSpecificRole(TSRId, TSRName, Description, CTime, RoleId, ManagerId)
Candidate Keys	[1] TSRId, [2] RoleId
Foreign Keys	[1] RoleId references Role(RoleId), [2] ManagerId references TeamManager(ManagerId)
Nullable Attributes	Description
Non-nullable Attributes	TSRId, TSRName, CTime, RoleId, ManagerId
Notes	[1] TSRId is created as a surrogate primary key.
Normalization Analysis	[FD]: [1] TSRId -> TSRName, Description, CTime, RoleId, ManagerId; [2] RoleId -> TSRId [Highest NF]: BCNF
9	StandardRole(SRId, SRName, RoleId)
Candidate Keys	[1] SRId, [2] SRName, [3] RoleId
Foreign Keys	[1] RoleId references Role(RoleId)
Nullable Attributes	
Non-nullable Attributes	SRId, SRName, RoleId
Notes	[1] SRId is created as a surrogate primary key.

Normalization Analysis	[FD]: [1] SRId -> SRName, RoleId; [2] SRName -> SRId; [3] RoleId -> SRId [Highest NF]: BCNF
10	TeamMemberRole(TMRId, TMId, RoleId)
Candidate Keys	[1] TMRId, [2] TMId, RoleId
Foreign Keys	[1] TMId references TeamMember(TMId), [2] RoleId references Role(RoleId)
Nullable Attributes	
Non-nullable Attributes	TMRId, TMId, RoleId
Notes	[1] TMRId is created as a surrogate primary key.
Normalization Analysis	[FD]: [1] TMRId -> TMId, RoleId; [2] TMId, RoleId -> TMRId [Highest NF]: BCNF
11	ProjectStatus(PSId, PSName, Description)
Candidate Keys	[1] PSId
Foreign Keys	
Nullable Attributes	Description
Non-nullable Attributes	PSId, PSName
Notes	[1] PSId is created as a surrogate primary key.
Normalization Analysis	[FD]: [1] PSId -> PSName, Description [Highest NF]: BCNF
12	Project(ProjectId, PName, Description, ExpCompTime, ActCompTime, CurrentStatusId, ParentProjectId, TeamId, CreatorManagerId, AssigneeTMId)
Candidate Keys	[1] ProjectId
Foreign Keys	[1] CurrentStatusId references Status(StatusId), [2] CreatorManagerId references Manger(ManagerId), [3] AssigneeTMId references TeamMember(TMId), [4] ParentProjectId references Project(ProjectId), [5] TeamId references Team(TeamId)
Nullable Attributes	ParentProjectId, AssigneeTMId
Non-nullable Attributes	ProjectId, PName, Description, ExpCompTime, ActCompTime, TeamId, CreatorManagerId, CurrentStatusId
Notes	
Normalization Analysis	[FD]: [1] ProjectId -> PName, Description, ExpCompTime, ActCompTime, CurrentStatusId, ParentProjectId, TeamId, CreatorManagerId, AssigneeTMId [Highest NF]: BCNF
13	Status(StatusId, ProjectId, PSId, PStime)
Candidate Keys	[1] StatusId, [2] ProjectId, PSId, PStime
Foreign Keys	[1] ProjectId references Project(ProjectId), [2] PSId references ProjectStatus(PSId)
Nullable Attributes	
Non-nullable Attributes	Status, ProjectId, PSId, PStime
Notes	
Normalization Analysis	[FD]: [1] StatusId -> ProjectId, PSId, PStime; [2] ProjectId, PSId, PStime -> StatusId [Highest NF]: BCNF